



Material Safety Data Sheet

Kwik Kleen Prem Solvent 145

Part Number: 17H0320511

Hukill Chemical Corporation

7013 Krick Road

Bedford, OH 44146-4493

Section I: Chemical Product & Company Identification

Manufacturer	Hukill Chemical Corporation 7013 Krick Road Bedford, OH 44146-4493	Emergency Telephone Number	(800) 962-1143	
		Chemtrec's Telephone Number	(800) 424-9300	
		Prepared By	Ed Potoma	
Telephone Number	(440) 232-9400	Date Prepared	August 24, 2001	
Fax Number	(440) 232-9477	HMIS	Health	2
Web Site	http://www.hukill.com		Flammability	2
Email	hukill@hukill.com		Reactivity	0
Synonyms				

Section II: Composition/Information On Ingredients

Hazardous Components	Reportable Under SARA Section 313	CAS Number	OSHA Limits (ppm)			ACGIH TLV (ppm)	%
			PEL	STEL	Ceiling		
Petroleum distillates (naphtha)	No	8002-05-9	500	N/A	N/A	N/A	100
<i>* mg/m³ instead of ppm.</i>							

Section III: Hazardous Identification

Emergency Overview:							
Route(s) of Entry	Inhalation?	Yes	Skin?	Yes	Ingestion?	Yes	
Health Hazards (Acute and Chronic)							
Liquid is severely irritating to eyes and irritating to skin. Inhalation of high concentration is may cause CNS depression. Liquid is moderately toxic and may be harmful if swallowed. Preexisting eye, skin and respiratory disorders may be aggravated.							
Signs and Symptoms of Exposure							
Irritation as noted above. Earley CNS depression may be evidenced by headache, dizziness and nausea. In extreme cases death may occure.							
Carcinogenicity	NTP	No	IARC Monographs	No	OSHA Regulated?	No	
Comments	None.						

Section IV: First Aid

Eye Contact	
Skin Contact	
Inhalation	
Ingestion	



Material Safety Data Sheet

Kwik Kleen Prem Solvent 145

Part Number: 17H0320511

Hukill Chemical Corporation

7013 Krick Road

Bedford, OH 44146-4493

Section V: Fire Fighting Measures

Flash Point (method used)	Flammable Limits	LEL	UEL
> 145 F		N/A	N/A
Extinguishing Media	Use water fog, foam, dry chemical or CO2.		
Special Fire Fighting Procedures			
Warning. Combustible. Clear fire area of unprotected personnel. Cool fire exposed containers. Use self-contained breathing apparatus for confined areas.			
Unusual Fire and Explosion Hazards			
Cool containers exposed to intense heat with water to prevent container rupture from vapor pressure build-up.			

Section VI: Accidental Release Measures

Steps to Be Taken in Case Material is Released or Spilled
Keep liquid and vapour away from heat, sparks and flame. Handling equipment must be grounded to prevent sparking. Shut off source of leak if safe to do so. Dike and contain. Clean up residue with absorbents. Flush spill area with water.
Waste Disposal Method
Waste material is considered hazardous under EPA-RCRA (40 FR 261.33). Follow latest EPA or State regulations regarding proper disposal.

Section VII: Handling And Storage

Precautions to Be Taken in Handling and Storing
Keep liquid and vapor away from heat, sparks and flame. Empty containers can contain explosive vapor. Avoid static electricity by grounding equipment.
Other Precautions
Bond and ground transfer equipment.

Section VIII: Exposure Controls, Personal Protection

Respiratory Protection (Specify)	Air-purifying respirator for organic vapor or air-supplying respirator.			
Ventilation	Local Exhaust	Use explosion-proof ventilation as required.		
	Mechanical (General)	Use explosion-proof ventilation as required.		
	Special	None	Other	None
Protective Gloves	Chemical resistant.			
Eye Protection	Safety glasses or Goggles			
Other Protective Clothing or Equipment				
Use explosion-proof ventilation as required to control vapor concentration				
Work/Hygienic Practices				
Explosion-proof ventilation. Air dry contaminated clothing in a well ventilated area.				



Material Safety Data Sheet

Kwik Kleen Prem Solvent 145

Part Number: 17H0320511

Hukill Chemical Corporation

7013 Krick Road

Bedford, OH 44146-4493

Section IX: Physical And Chemical Properties

Boiling Point	N/A	Specific Gravity (H2O = 1)	N/A
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (Air = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility In Water	N/A		
Appearance and Odor	State		Liquid
Cloudy liquid. Mineral spirit odor.			

Section X: Stability And Reactivity

Stability	Conditions to Avoid	Avoid sparks, heat, flame, strong oxidizing agents, alkali metal hydroxides
Stable		
Incompatibility (Material to Avoid)	Avoid strong oxidizing agents	
Hazardous Decomposition of Byproducts	Carbon monoxide and unidentified organics may be formed during combustion	
Hazardous Polymerization	Conditions to Avoid	None.
Will not occur		

DOT Shipping Name: Combustible Liquid, N.O.S. (Petroleum Distillates)

Hazard Class: 99

UN Number: NA1993

PGIII

The information contained herein has been approved by Hukill Chemical Corporation and is offered only as a guide to the handling of this specific material and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive and the manner and conditions of use and handling may involve other and additional considerations. No warranty of any kind is given or implied and Hukill Chemical Corporation will not be liable for any damages, losses, injuries or consequential damages that may result from the use or reliance of any information contained herein.